

PROJECT: **BUILDING 900S AREA**
Presidio of San Francisco, California

Log of Monitoring Well 937GW101

PAGE 1 OF 1

Boring location: See Figure 5 *

Date started: 6/20/01

Date finished: 6/20/01

Drilling method: Hand auger to 5 feet, then switch to Hollow stem

Logged by: C. Keane

Drilled by: Gregg Drilling

Coordinates: Northing: 481615.32

Easting: 1431637.27

Hammer weight/drop: 140lbs./36-inches

Hammer type: Downhole

Sampler: Split Spoon

DEPTH (feet)	SAMPLES				OVM (ppm)	LITHOLOGY	MATERIAL DESCRIPTION	WELL COMPLETION INFORMATION
	Sample Number	Sample	Blow Count	Recovery (feet)				
							Top of Casing Elevation: 11.81 ¹	
1							SAND (SP) medium brown, loose, moist, poorly-graded	
2								
3								
4			4		0.1			Protective casing to feet above ground surface
5			7					2-inch dia., SCH 40 PVC Blank From 0 To 5 Feet
6			12					Grout From 0 To 3 Feet
7								Bentonite From 3 To 4 Feet
8						SP		
9			7				dark gray coarse grained	
10			26		1.1		medium dense, moist	2-inch dia., SCH 40 PVC Screened Casing From 5 To 15 feet
11			40					
12								
13							wet	
14			14		0.9			Sand From 4 To 15 Feet
15			26					
16			50					
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								
35								

Boring terminated at 15 feet below ground surface. Boring converted to groundwater monitoring well. No groundwater encountered.

¹ Elevation based on 16 & 17 August 2001 survey by Towill, Inc. to Presidio Lower Low Water datum.

* Draft Building 900s Area Construction Completion Report (Treadwell & Rollo, 2003).

Treadwell & Rollo

Project No:

2893.08

Figure:

A-12